



Anybus X-gateway IIoT – Modbus TCP Server - OPC UA-MQTT

The Anybus X-gateway IIoT allows you to seamlessly inter-connect PLC control systems and their connected devices to the IIoT networks MQTT and OPC UA.

SAFE AND ISOLATED DATA MONITORING

The X-gateway IIoT's primary function is to allow the fast streaming of an industrial network into OPC UA and MQTT. This offloads your PLC from working with additional services while providing extra security by isolated the high-risk connections away from sensitive areas. In principle, the PLC gets its own firewall.

EASY CONFIGURATION - NO PROGRAMMING REQUIRED!

The connection between the two networks is quickly set up in the Anybus Configuration Manager software, included with the X-gateway. No programming skills are needed to set up the X-gateway.



Features and benefits

- Supports OPC UA micro-embedded profile
- Supports Discovery Services
- User name and password authentication
- Supports DataChange Subscription
- MQTT client acting as publisher
- Proven and tested with PLC's from all leading manufacturers
- Possibility to build web pages to display and control a factory floor

Modbus TCP Slave interface

Modbus TCP Slave settings can be made either via the built-in web interface, or by importing the provided .EDS file into engineering tool of the controlling PLC.

- Conforms to Modbus TCP v1.0
- Modbus TCP class 0, class 1 and partially class 2 slave functionality
- 10/100Mbit operation in full or half-duplex
- Integrated FTP server provides easy file management using standard FTP clients
- Web server with dynamic data capability and Server Side Include (SSI) capability
- Email client with dynamic data capability and Event-triggered email handling
- Per-user security framework
- Quality of Service (QoS) available


- DNS Capability
- TCP/IP settings via DHCP/ARP/Anybus IPconfig (HICP)
- Integrated switch allowing for a daisy-chain topology
- 2x RJ-45 ports available simultaneously.

OPC UA

- Support for micro-embedded profile
- Data direction from server to client
- Supports Discovery Services
- Timestamp supported via discovery server
- User name and password authentication
- Supports DataChange Subscription
- Maximum 80 data point tags
- Dual port cut-through switch
- Dual RJ-45 ports available simultaneously

MQTT

- MQTT client acting as publisher
- MQTT version 3.1.1 supported
- Json data encoding supported
- QoS 0-2 supported
- User name and password authentication
- Maximum 256 data point tags
- Dual port cut-through switch
- Dual RJ-45 ports available simultaneously



TECHNICAL SPECIFICATIONS

Dimensions (L•W•H)	114 x 44 x 127mm or 4,49 x 1,73 x 5,00"
Weight	400g or 0,880 lbs
Operating temperature	-25 to +65 °C or -13 to +149 °F
Storage temperature	-40 to +85 °C or -40 to +185 °F
Power supply	24 VDC +/- 20% via 2-pole 5.08 mm Phoenix pluggable screw connector
Current consumption	max. 400mA (Typical 200mA)

Enclosure material	Aluminium and plastic
Installation position	Vertical / Flat*
Galvanic isolation	YES, on both BUS/Ethernet side
Mechanical rating	IP20, NEMA rating 1
Mounting	DIN-rail (EN 50022 standard)
I/O configuration	via USB port with Anybus Configuration Manager software
Certifications	CE, CULUS, RoHS

Ordering information

Order Code	AB7555
Included components	Gateway Quick start documentation USB configuration cable Power supply not included Configuration software is available for download.

3 year guarantee. For purchasing instructions and terms and conditions, see: [How to buy](#).

Copyright © 2020 HMS Industrial Networks - All rights reserved.