



## Anybus X-gateway – Modbus RTU – Modbus RTU Slave

The Anybus X-gateway allows you to seamlessly inter-connect/extend PLC control systems and their connected devices on a Modbus RTU network.

### FAST COPYING OF I/O DATA

The X-gateways primary function is with the fast transfer of cyclic I/O data between the two networks. This offloads your PLC from working with additional calculations. The gateway acts as a Slave on both sides of the Modbus RTU network and provides a simple network extension. The data transmission between the two networks is completely transparent with a maximum data capacity of 512 bytes in each direction.

### EASY CONFIGURATION - NO PROGRAMMING REQUIRED!

The connection between the two networks is quickly set up in the Anybus Configuration Manager software, included with the X-gateway. No programming skills are needed to set up the X-gateway. As factory default the X-gateways have a pre-defined I/O size of 20 bytes I/O.



## Features and benefits

- Fast copying of cyclic I/O data between two Modbus RTU networks (10-15 ms)
- Proven and tested with all PLC manufacturers
- Supports up to a maximum of 512 bytes of Input and Output data in each direction
- Optional control and status information added to the I/O data for diagnostic purposes
- Robust stand-alone housing for use in harsh industrial environments
- Global free technical support and consultancy

## Modbus RTU Slave interface

Modbus RTU network address settings made via on-board configuration switches

- Complete Modbus RTU slave functionality
- Max 512 bytes of Input and 512 bytes of Output data
- Modbus diagnostics support
- Configuration via on-board DIP switches
- Modbus RTU baudrate 12-57,6 kbit/s
- 1x D-sub 9-pin female network connector

## Modbus RTU Slave interface

Modbus RTU network address settings made via on-board configuration switches

- Complete Modbus RTU slave functionality
- Max 512 bytes of Input and 512 bytes of Output data
- Modbus diagnostics support
- Configuration via on-board DIP switches

- Modbus RTU baudrate 12-57,6 kbit/s
- 1x D-sub 9-pin female network connector



## TECHNICAL SPECIFICATIONS

<b>Dimensions (L•W•H)</b>	114 x 44 x 127mm or 4,49 x 1,73 x 5,00"
<b>Weight</b>	400g or 0,880 lbs
<b>Operating temperature</b>	-25 to +65 °C or -13 to +149 °F
<b>Storage temperature</b>	-40 to +85 °C or -40 to +185 °F
<b>Power supply</b>	24 VDC +/- 20% via 2-pole 5.08 mm Phoenix pluggable screw connector
<b>Current consumption</b>	max. 400mA (Typical 200mA)
<b>Enclosure material</b>	Aluminium and plastic
<b>Installation position</b>	Vertical / Flat*
<b>Galvanic isolation</b>	YES, on both BUS/Ethernet side
<b>Mechanical rating</b>	IP20, NEMA rating 1
<b>Mounting</b>	DIN-rail (EN 50022 standard)
<b>I/O configuration</b>	via USB port with Anybus Configuration Manager software
<b>Certifications</b>	CE, cULUS, RoHS

## Ordering information

<b>Order Code</b>	AB7899
<b>Included components</b>	<p>Gateway</p> <p>Quick start documentation</p> <p>USB configuration cable</p> <p>Power supply <b>not</b> included</p> <p>Configuration server software is available for download.</p>

3 year guarantee. For purchasing instructions and terms and conditions, see: [How to buy](#).

Copyright © 2020 HMS Industrial Networks - All rights reserved.