


## Technical Data - 4 CH Relay Module (101-210210)

Technical Data - 4 Channel Relay Module (101-210210)	
<b>Backplane</b>	
Controllers	Web server, PROFINET IO device, PROFIBUS DP slave
Modules	32 (all slots)
Power supply	Provided through the backplane
Current consumption	± 225 mA (465 mA max)
Compatible backplane units	101-200011, 101-200012, 101-200023, 101-200024, 101-200027
<b>Relays</b>	
Relays	4 (2 on the front, and 2 on the bottom)
Current	5 A per relay
Voltage	230 VAC
Resistance	300 mOhm (including connectors)
Toggles	100000 (at 5A - 230 VAC)
<b>Connectors</b>	
Pins	1 = No (normally open) 2 = Common 3 = Nc (normally closed)
Wire diameter (for the screw terminals)	< 2.5 mm <sup>2</sup>
Wire type	Stranded or solid core
	
<b>Others</b>	
Head Station firmware	V1.260 and later
Dimensions	140 x 110 x 25 mm
Operating temperature	0 .. 60 °C
Weight	125 g
MTBF	To be defined
<b>PROCENDEC</b> Klopperman 16 2292 JD WATERINGEN (NL)	<b>Tel.: +31-174-671800</b> <b>Fax: +31-174-671801</b> <b>Email: info@procentec.com</b>